



## K-Flex ST plus Technical Data Sheet

**Description:** Highly flexible closed cell elastomeric foam (FEF) suitable for hot and cold thermal insulation, featuring a combination of low thermal conductivity, high water vapour diffusion resistance and low flame spread.

**Applications:** Thermal insulation for pipes, ducts, tanks, applied for refrigeration, air conditioning, heating and plumbing, pipe fittings and water ducts, industrial applications for energy saving and/or condensation prevention purposes.

**Brand names:** "K-Flex ST Plus" sold as tubes, sheets, tape and self adhesive sheets  
"K-Flex ST Plus/SK" sold in precut self adhesive pipes

### Physical properties:

Property	Value	Notes
Maximum service temperature Tubes (EN14707): Sheets (EN14706): Self adhesive pipes:	+110°C +85°C +85°C	
Minimum service temperature	-40°C	For industrial applications, product can be applied down to -198°C; for applications below -40°C please contact our technical department
Water vapour diffusion resistance (EN 12086) Tubes/Sheets thickness ≤ 25mm Tubes/Sheets thickness >25mm, tapes, Duct	$\mu \geq 10\ 000$ $\mu \geq 7\ 000$	
Water absorption (EN 13472)	<0.1 %	
Leachable chlorides (EN 13468)	<500 ppm	When tested in line with DIN1988/7, leachable chlorides <0.05%
Ph (EN 13468)	Neutral (7±1)	
Reaction to fire (EN13501)	B, s3, d0 BL, s3, d0	(sheets, self adhesive sheets 3 to 50mm, 3mm tapes) (tubes, up to 75mm)
Dimensional tolerances	as per EN14304	

	Medium temperature [°C]	-30	-20	-10	0	10	20	30	40	50	70
Tubes thickness ≤ 25mm (EN ISO 8497)	Thermal conductivity [W/(m °K)]	0.030	0.031	0.032	0.033	0.034	0.035	0.036	0.037	0.0385	0.042
Tubes thickness > 25mm (EN ISO 8497)	Thermal conductivity [W/(m °K)]	0.033	0.034	0.035	0.036	0.037	0.038	0.039	0.040	0.041	0.043
Sheets thickness ≤ 25mm (EN 12667)	Thermal conductivity [W/(m °K)]	0.030	0.031	0.032	0.033	0.034	0.035	0.036	0.037	0.0385	0.042
Sheets thickness > 25mm (EN 12667)	Thermal conductivity [W/(m °K)]	0.033	0.034	0.035	0.036	0.037	0.038	0.039	0.040	0.041	0.043

Roncello, 24/06/2012; K-Flex ST Plus technical datasheet n° 2 rev.3

**L'ISOLANTE K-FLEX S.r.l.**

**L'ISOLANTE K-FLEX S.R.L.**  
Sede Legale Stabilimento e uffici  
Via Leonardo da Vinci, 36  
20040 RONCELLO (MB)  
Codice Fiscale/09470180150  
Partita IVA 02423640966

Via Leonardo Da Vinci, 36  
20877 Roncello (MB) - Italy  
Tel.: +39 039.6824.1 (r.a.)  
fax: +39 039.6824500  
[www.kflex.com](http://www.kflex.com) - [info@isolante.com](mailto:info@isolante.com)

Cap. Soc. € 25.200.000 i.v.  
Codice fiscale 09470180150  
Partita IVA IT 02423640966  
Reg. Imp. Monza e Brianza n. MB 09470180150  
R.E.A. 1868777